

Flambeau Broadcasting Company

Ladysmith, Wisconsin

O. J. Falge, President

A. T. Shields, Manager

April 6, 1953

Mr. J. W. Brauner
23 Howard Ave
Williamsville 21, New York

Dear Mr. Brauner:

Much thanks for your recent letter reporting reception of WLDY during our recent equipment and frequency test program.

We operate on the schedule of the first Friday of every month from 12:30 AM to 1 AM CST with Boyd Phelps Laboratories of Minneapolis. Therefore, our next check will be on the morning of May 1, 1953.


WLDY uses a 200 foot self supporting antenna, current fed and with an excellent ground system helped along by the fact that the tower is located in the middle of a swamp.

Please consider this letter verification of your reception of WLDY the morning of April 3, 1953 from 12:30 AM to 1 AM CST.

If there is anything more I can do please don't hesitate to call on me.

30 and 73's OM

JE:je


Jeff Evans,
Chief Engineer
Ex-W2TSO

P.S. WLDY usually modulates the carrier during these tests with a 1000 cycle tone derived from the General Radio Freq Monitor whose crystal beats against our xmtr freq.

250 Watts - 1340 Kilocycles

North Central Wisconsin's Leading Independent

REPRESENTED NATIONALLY BY THOMAS F. CLARK CO., Inc., NEW YORK, CHICAGO
ORVILLE LAWSON AND ASSOCIATES, MINNEAPOLIS

W
L
D
Y