

KVRS

1000 WATTS



WYOMING BROADCASTING CO., ROCK SPRINGS, WYOMING

DWIGHT A. FISHER
MANAGER

LAUREL H. MOSBEY
COMMERCIAL MANAGER

February 19, 1958

Maurice W. Nittler
2818 South Cherokee
Englewood, Colorado

Mr Nittler

Thanks for the report. It's a pleasure to hear from you. This is one of only a very few reports from your area. Undoubtably your report is correct, of our frequency check February 18, 1958 from 1:15 until 1:30 am MST.

You might be interested in knowing we operate on 1360 kc from 7:00 am to 10:30 pm except sundays, which is from 8:00 am to 10:00 pm. Our regular frequency check is held each month, scheduled by the Commercial Monitoring Co. in Kansas City, Mo. We operate on full power for the Checks.

Xmtr is a Collins Type 20-T, direct crystal control. Last stage: Two 500 watt vacuum tubes for high level Modulation. Maximum rated carrier output one Kilowatt of power.

Antenna consists of two, 200 ft. triangular uniform cross-section guyed, series excited, vertical type. Spacing is 560 ft. on a line bearing 192° true. North tower used for 1,000 watt non-directional operation between sunrise and Sunset (Local Time). Nighttime operation is 500 watts directional pattern.

Hope this is the information you want. Thanks again for writting.

S. C. WOOD
For John Gormana
Chief Engineer